LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 50/40

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 50/40

Bestektekst

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN50/40



Artikelgegevens

EAN-code	**4038088093153**
ETIM Klasse	**EC003025**
Nominale diameter	**DN 50, DN 40**
Nominale lengte/graad	**45**
Buitenafmetingen (HxBxL)	**89 x 198 x 227 mm**
Gewicht	**1,50 Kg (STK)**
Productgroep	**3**
Douanetariefnummer	**73089098**
Materiaal / Kleur	**Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Downloads

Alles online

Installatiehandleiding (PDF)
CAD 2D (DXF)
Maattekening (PDF)
CAD (DWG)
Brochure (PDF)