

## LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 100/40

LORO-Composite Pipe-Red. branches SILENT 45 degrees DN 100/40

### Text pentru caietul de sarcini

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN100/40



### Date articol

|                               |                             |
|-------------------------------|-----------------------------|
| Cod EAN                       | 4038088093207               |
| Clasă ETIM                    | EC003025                    |
| Diametru nominal              | DN 100, DN 40               |
| Lungime/grad nominal          | 45                          |
| Dimensiuni exterioare (ÎxLxA) | 133 x 232 x 280 mm          |
| Greutate                      | 6,00 Kg (STK)               |
| Grupă de produse              | 3                           |
| Număr tarif vamal             | 73089098                    |
| Material / Culoare            | Stahl feuerverzinkt, Silber |

### Notă de utilizare

Silent für erhöhte Schallschutzanforderungen  
Doppelwandiges Abflussrohr, DN 40 - DN 150  
bestehend aus:Innenrohr mit Schallschutzfolie,PU-  
Dämmschicht, Baustoffklasse B2, FCKW-  
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X  
Stahlabflussrohr) Achtung: Sonderanfertigung - keine  
Lagerware.

### Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[Broșură \(PDF\)](#)