


LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 125/50

LORO-Composite Pipe-Red. branches SILENT 45 degrees DN 125/50

Beskrivningstext

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN125/50



Artikeldata

EAN-kod	4038088093221
ETIM-klass	EC003025
Nominell diameter	DN 125, DN 50
Nominell längd/grad	45
Yttermått (HxBxL)	168 x 305 x 365 mm
Vikt	7,00 Kg (STK)
Produktgrupp	3
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[Broschyr \(PDF\)](#)