

LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 150/70

LORO-Composite Pipe-Red. branches SILENT 45 degrees DN 150/70

Besedilo za popis del

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN150/70

Podatki o izdelku

EAN koda	4038088093245
ETIM razred	EC003025
Nazivni premer	DN 150, DN 70
Nazivna dolžina/stopinja	45
Zunanje mere (VxŠxD)	219 x 338 x 335 mm
Teža	13,00 Kg (STK)
Skupina izdelkov	3
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)

[Prospekt \(PDF\)](#)