LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 150/70

LORO-Composite Pipe-Red. branches SILENT 45 degrees DN 150/70

Texto para caderno de encargos

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN150/70

Dados do artigo

Código EAN	**4038088093245**
Classe ETIM	**EC003025**
Diâmetro nominal	**DN 150, DN 70**
Comprimento/grau nominal	**45**
Medidas exteriores (AxLxP)	**219 x 338 x 335 mm**
Peso	**13,00 Kg (STK)**
Grupo de produtos	**3**
Número de pauta aduaneira	**73089098**
Material / Cor	**Stahl feuerverzinkt, Silber**

Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Transferências

Instruções de instalação (PDF)

Brochura (PDF)

Alles online