LORO-X SILENT COMPOSITE REDUCED BRANCH 45 DEGREE DN 150/125

LORO multilayer pipe red. branches SILENT 45 degrees DN 150/125

Beschrijving

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN150/125



Artikelgegevens

EAN-code	4038088038390
ETIM Klasse	EC003025
Nominale diameter	DN 150, DN 125
Nominale lengte/graad	45
Buitenafmetingen (HxBxL)	219 x 385 x 420 mm
Gewicht	15,00 Kg (STK)
Productgroep	3
Douanetariefnummer	73089098
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Downloads

Alles online

Installatiehandleiding (PDF)
CAD 2D (DXF)
Maattekening (PDF)
CAD (DWG)
Brochure (PDF)