

#NV

#NV

Kiírási szöveg

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN200/100

Cikkadatok

EAN kód	#NV
ETIM osztály	EC003025
Névleges átmérő	DN #NV, DN #NV, DN #NV
Névleges hossz/fok	#NV
Külső méretek (MxSzxH)	#NV x #NV x #NV mm
Súly	#NV Kg (STK)
Termékcsoport	#NV
Vámtarifaszám	#NV
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)[Prospektus \(PDF\)](#)