

LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 80/40

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 80/40

Текст за тържна документация

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN 80/40

Данни за артикула

ЕАН код	4038088093177
ЕТИМ клас	EC003025
Номинален диаметър	DN 80, DN 40
Номинална дължина/градус	45
Външни размери (ВхШхД)	133 x 242 x 240 mm
Тегло	3,50 Kg (STK)
Продуктова група	3
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)

[Брошура \(PDF\)](#)