

LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 80/70

LORO-Composite Pipe-Red. branches SILENT 45 degrees DN 80/70

Tekst przetargowy

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN 80/70

Dane artykułu

Kod EAN	4038088093191
Klasa ETIM	EC003025
Średnica nominalna	DN 80, DN 70
Długość/stopień nominalny	45
Wymiary zewnętrzne (WxSxD)	133 x 240 x 260 mm
Waga	4,70 Kg (STK)
Grupa produktów	3
Numer taryfy celnej	73089098
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)

[Broszura \(PDF\)](#)