

LORO-VERBUNDROHR-BOGEN SILENT 87 GR.

LORO-Composite pipe bend SILENT 87 degrees DN 40

Texto de licitación

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 87 degrees, DN40



Datos del artículo

Código EAN	4038088089965
Clase ETIM	EC003024
Diámetro nominal	DN 40
Longitud/grado nominal	87
Medidas exteriores (AxAxL)	89 x 169 x 173 mm
Peso	1,30 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[Folleto \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)