

LORO-X SILENT COMPOSITE BEND 87 DEGREE DN 125

LORO-Composite pipe bend SILENT 87 degrees DN 125

Descriere

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 87 degrees, DN125




Date articol

Cod EAN	4038088026236
Clasă ETIM	EC003024
Diametru nominal	DN 125
Lungime/grad nominal	87
Dimensiuni exterioare (îxLxA)	168 x 260 x 272 mm
Greutate	6,00 Kg (STK)
Grupă de produse	3
Număr tarif vamal	73089098
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Desen CAD \(PDF\)](#)

[CAD \(DWG\)](#)

[Broșură \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)