

LORO-X SILENT COMPOSITE BEND 70 DEGREE DN 80

LORO-Composite pipe bend SILENT 70 degrees DN 80

Udbudstekst

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 70 degrees, DN 80

Artikeldata

EAN-kode	4038088093115
ETIM Klasse	EC003024
Nominal diameter	DN 80
Nominal længde/grad	70
Ydermål (HxBxL)	133 x 281 x 305 mm
Vægt	3,90 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73089098
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[Brochure \(PDF\)](#)

[BIM IFC4 \(parametrisk\)](#)