LORO-X SILENT COMPOSITE BEND 70 DEGREE DN 80

LORO-Composite pipe bend SILENT 70 degrees DN 80

Texte de prescription

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 70 degrees, DN 80

Données de l'article

Code EAN	**4038088093115**
Classe ETIM	**EC003024**
Diamètre nominal	**DN 80**
Longueur/degré nominal	**70**
Dimensions extérieures (HxLxP)	**133 x 281 x 305 mm**
Poids	**3,90 Kg (STK)**
Groupe de produits	**3**
Numéro tarifaire douanier	**73089098**
Matériau / Couleur	**Stahl feuerverzinkt, Silber**

Note d'utilisation

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Téléchargements

Alles online

Notice d'installation (PDF)

Brochure (PDF)

BIM IFC4 (parametrisch)