

LORO-X SILENT COMPOSITE BEND 45 DEGREE DN 32

LORO-Composite pipe bend SILENT 45 degrees DN 32

Κείμενο προδιαγραφών

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN32




Στοιχεία προϊόντος

Κωδικός EAN	4038088093092
Κατηγορία ETIM	EC003024
Ονομαστική διάμετρος	DN 32
Ονομαστικό μήκος/μοίρες	45
Εξωτερικές διαστάσεις (ΥxΠxΜ)	89 x 125 x 155 mm
Βάρος	0,60 Kg (STK)
Ομάδα προϊόντων	3
Δασμολογικός αριθμός	73089098
Υλικό / Χρώμα	Stahl feuerverzinkt, Silber

Σημείωση χρήσης

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Λήψεις



Alles online

[Οδηγίες εγκατάστασης \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Σχέδιο διαστάσεων \(PDF\)](#)

[CAD \(DWG\)](#)

[Φυλλάδιο \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)