

LORO-X SILENT COMPOUND BEND 45 DEGREE DN 80

LORO-Composite pipe bend SILENT 45 degrees DN 80

Texto para caderno de encargos

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN 80

Dados do artigo

Código EAN	4038088093108
Classe ETIM	EC003024
Diâmetro nominal	DN 80
Comprimento/grau nominal	45
Medidas exteriores (AxLxP)	133 x 229 x 298 mm
Peso	3,20 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Brochura \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)