
LORO-X SILENT COMPOSITE BEND 30 DEGREE DN 50

LORO-Composite pipe bend SILENT 30 degrees DN 50

Kuvaus

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 30 degrees, DN50





Tuotetiedot

EAN-koodi	4038088026359
ETIM-luokka	EC003024
Nimellishalkaisija	DN 50
Nimellispituus/-aste	30
Ulkomitat (KxLxS)	89 x 134 x 203 mm
Paino	1,10 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Lataukset

Alles online

Asennusohje (PDF)
Mittapiirustus (PDF)
Esite (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)