# LORO-X SILENT COMPOSITE BEND 30 DEGREE DN 80

**LORO-Composite pipe bend SILENT 30 degrees DN 80**

## Text pro výběrové řízení

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 30 degrees, DN 80

## Údaje o artiklu

| | |
|---|---|
| EAN kód | 4038088093061 |
| ETIM třída | EC003024 |
| Jmenovitý průměr | DN 80 |
| Jmenovitá délka/stupeň | 30 |
| Vnější rozměry (VxŠxD) | 133 x 197 x 276 mm |
| Hmotnost | 3,30 Kg (STK) |
| Skupina produktů | 3 |
| Celní sazebník | 73089098 |
| Materiál / Barva | Stahl feuerverzinkt, Silber |

## Pokyny k použití

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

## Ke stažení

Alles online

Návod k instalaci (PDF)

Prospekt (PDF)

BIM IFC4 (parametrisch)