

LORO-X SILENT COMPOSITE BEND 30 DEGREE DN 100

LORO-Composite pipe bend SILENT 30 degrees DN 100

Kuvaus

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 30 degrees, DN100




Tuotetiedot

EAN-koodi	4038088026373
ETIM-luokka	EC003024
Nimellishalkaisija	DN 100
Nimellispituus/-aste	30
Ulkomitat (KxLxS)	133 x 181 x 246 mm
Paino	3,30 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-
Dämmschicht, Baustoffklasse B2, FCKW-
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X
Stahlabflussrohr) Achtung: Sonderanfertigung - keine
Lagerware.



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

CAD 2D (DXF)

[Mittapiirustus \(PDF\)](#)

CAD (DWG)

[Esite \(PDF\)](#)

BIM IFC4 (parametrisch)