LORO-X SILENT COMPOSITE BEND 15 DEGREE DN 70

LORO-Composite pipe bend SILENT 15 degrees DN 70

Beskrivelse

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 15 degrees, DN70



Artikkeldata

EAN-kode	4038088026410
ETIM-klasse	EC003024
Nominell diameter	DN 70
Nominell lengde/grad	15
Utvendige mål (HxBxL)	102 x 127 x 204 mm
Vekt	1,60 Kg (STK)
Produktgruppe	3
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Nedlastinger

Alles online

Monteringsanvisning (PDF)
Måltegning (PDF)
Brosjyre (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)