LORO-X SILENT COMPOSITE BEND 15 DEGREE DN 80

LORO-Composite pipe bend SILENT 15 degrees DN 80

Text pro výběrové řízení

LORO-X compound pipe bend, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 15 degrees, DN 80

Údaje o artiklu

EAN kód	**4038088093078**
ETIM třída	**EC003024**
Jmenovitý průměr	**DN 80**
Jmenovitá délka/stupeň	**15**
Vnější rozměry (VxŠxD)	**133 x 164 x 239 mm**
Hmotnost	**2,30 Kg (STK)**
Skupina produktů	**3**
Celní sazebník	**73089098**
Materiál / Barva	**Stahl feuerverzinkt, Silber**

Pokyny k použití

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Ke stažení

Alles online

Návod k instalaci (PDF)

Prospekt (PDF)

BIM IFC4 (parametrisch)