

LORO-VERBUND-RED.ÜBERGANGSROHR SILENT,

LORO-Connection Red.-transition pipe SILENT DN 40/50

Tarjouspyyntöteksti

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN40/50



Tuotetiedot

EAN-koodi	4038088090046
ETIM-luokka	EC003024
Nimellishalkaisija	DN 40, DN 50
Ulkomitat (KxLxS)	89 x 89 x 115 mm
Paino	0,50 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-
Dämmschicht, Baustoffklasse B2, FCKW-
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X
Stahlabflussrohr) Achtung: Sonderanfertigung - keine
Lagerware.

Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[Esite \(PDF\)](#)