

## LORO-X SILENT COMPOUND TRANSITION PIPE CONCENTRIC DN 40/70

### LORO-Composite Red. transition pipe SILENT DN 40/70

#### Kiírási szöveg

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN40/70




#### Cikkadatok

|                       |                             |
|-----------------------|-----------------------------|
| EAN kód               | 4038088093276               |
| ETIM osztály          | EC003024                    |
| Névleges átmérő       | DN 40, DN 70                |
| Külső méretek (MxSxH) | 102 x 102 x 150 mm          |
| Súly                  | 0,70 Kg (STK)               |
| Termékcsoport         | 3                           |
| Vámtarifaszám         | 73089098                    |
| Anyag / Szín          | Stahl feuerverzinkt, Silber |

#### Használati megjegyzés

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



#### Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Méterrajz \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospektus \(PDF\)](#)