

LORO-X SILENT COMPOUND TRANSITION PIPE CONCENTRIC DN 40/70

LORO-Composite Red. transition pipe SILENT DN 40/70

Bestektekst

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN40/70




Artikelgegevens

EAN-code	4038088093276
ETIM Klasse	EC003024
Nominale diameter	DN 40, DN 70
Buitenafmetingen (HxBxL)	102 x 102 x 150 mm
Gewicht	0,70 Kg (STK)
Productgroep	3
Douanetariefnumme r	73089098

Materiaal / Kleur **Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Maattekening \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)