

LORO-X SILENT COMPOSITE TRANSITION PIPE CONCENTRIC DN 50/70

LORO-Composite Red. transition pipe SILENT DN 50/70

Descripción

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN50/70




Datos del artículo

Código EAN	4038088026472
Clase ETIM	EC003024
Diámetro nominal	DN 50, DN 70
Medidas exteriores (AxAxL)	102 x 102 x 148 mm
Peso	0,80 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD \(DWG\)](#)

[Folleto \(PDF\)](#)