

## LORO-X COMPOUND PIPE REDUCER, SILENT TYPE

LORO-Composite transition pipe

### Voce di capitolato

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN50/100



### Dati articolo

|                         |                             |
|-------------------------|-----------------------------|
| Codice EAN              | 4038088038673               |
| Classe ETIM             | EC003024                    |
| Diametro nominale       | DN 50, DN 100               |
| Peso                    | 1,50 Kg (STK)               |
| Gruppo prodotti         | 3                           |
| Numero tariffa doganale | 73089098                    |
| Materiale / Colore      | Stahl feuerverzinkt, Silber |

### Note d'uso

Silent für erhöhte Schallschutzanforderungen  
Doppelwandiges Abflussrohr, DN 40 - DN 150  
bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

### Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Brochure \(PDF\)](#)