

LORO-X SILENT COMPOUND TRANSITION PIPE CONCENTRIC DN 70/80

LORO-Composite Red. transition pipe SILENT DN 70/80

Texto para caderno de encargos

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN70/80

Dados do artigo

Código EAN	4038088093283
Classe ETIM	EC003024
Diâmetro nominal	DN 70, DN 80
Medidas exteriores (AxLxP)	133 x 133 x 185 mm
Peso	1,50 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Brochura \(PDF\)](#)