

LORO-X SILENT COMPOSITE TRANSITION PIPE CONCENTRIC DN 100/125

LORO-Composite Red. transition pipe SILENT DN 100/125

Leírás

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN100/125




Cikkadatok

EAN kód	4038088026496
ETIM osztály	EC003024
Névleges átmérő	DN 100, DN 125
Külső méretek (MxSzxH)	168 x 168 x 230 mm
Súly	3,50 Kg (STK)
Termékcsoport	3
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Méterrajz \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospektus \(PDF\)](#)