

LORO-X SILENT COMPOSITE TRANSITION PIPE CONCENTRIC DN 150/200

LORO-Composite SILENT transition pipe concentric

Beskrivningstext

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN150/200

Artikeldata

EAN-kod	4038088038437
ETIM-klass	EC003024
Nominell diameter	DN 150, DN 200
Yttermått (HxBxL)	273 x 273 x 315 mm
Vikt	10,40 Kg (STK)
Produktgrupp	3
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[Broschyr \(PDF\)](#)