

## LORO-X SILENT COMPOSITE TRANSITION PIPE CONCENTRIC DN 150/200

LORO-Composite SILENT transition pipe concentric

### Texto para caderno de encargos

LORO-X compound pipe transition pipe SILENT, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound-damping mat (attached to inner pipe), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), concentric reducer, DN150/200

### Dados do artigo

|                            |                             |
|----------------------------|-----------------------------|
| Código EAN                 | 4038088038437               |
| Classe ETIM                | EC003024                    |
| Diâmetro nominal           | DN 150, DN 200              |
| Medidas exteriores (AxLxP) | 273 x 273 x 315 mm          |
| Peso                       | 10,40 Kg (STK)              |
| Grupo de produtos          | 3                           |
| Número de pauta aduaneira  | 73089098                    |
| Material / Cor             | Stahl feuerverzinkt, Silber |

### Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

### Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Brochura \(PDF\)](#)