


## LORO-X TRANSITION PIECES WITH FLANGE DN 50

### LORO-X connecting piece with flange DN 50

## Description

LORO-X connector with flange and push-fit socket connection, according to DIN EN 1123, made of steel, hot-dip galvanized, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN50



## Article information

|                                     |                                    |
|-------------------------------------|------------------------------------|
| <b>EAN Code</b>                     | <b>4038088033609</b>               |
| <b>ETIM Class</b>                   | <b>EC003024</b>                    |
| <b>Nominal diameter</b>             | <b>DN 50</b>                       |
| <b>Outside measurements (HxWxL)</b> | <b>165 x 165 x 105 mm</b>          |
| <b>Weight</b>                       | <b>2,70 Kg (STK)</b>               |
| <b>Product group</b>                | <b>8</b>                           |
| <b>Customs tariff number</b>        | <b>73089098</b>                    |
| <b>Material / Color</b>             | <b>Stahl feuerverzinkt, Silber</b> |

### Usage note

kein Verwendungshinweis notwendig

## Downloads



Alles online

[Installation \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[CAD drawing \(PDF\)](#)

CAD 3D (DWG)

[Brochure \(PDF\)](#)

BIM 3D (STEP)