

LORO-X-BOX SIPHONIC SCUPPER ROOF DRAINAGE WITH 45 DEGREE CLAMMING-FLANGE PROOF OF PERFORMANCE AS DATA-SHEET LX480

LORO-X BOX Attika buckle outlet for pressurised water supply with clamping flange for bitumen DN 100

Popis

LORO-X BOX B0480.002X parapet siphonic drainage system DN100, consisting of main parapet drain with 45-degree clamping flange, horizontal offset, deflection with tight radius, anchor clips, sliding flange for the connection of the vapour barrier, sealing elements and lubricant for the complete assembly of the drain up to the downpipe. This parapet siphonic drainage system must be supplemented by the pressure-resistant LORO-X downpipe with a length of at least 4.2 m in order to achieve the specified performance. Please ask your dealer or your LORO contact person. Performance according to specification sheet LX480 at www.loro.de up to 16.2 l/s at 55 mm water level



Údaje o artikli

EAN kód	4038088090091
ETIM trieda	EC011350
Menovitý priemer	DN 100
Vonkajšie rozmery (VxŠxH)	190 x 270 x 935 mm
Hmotnosť	17,70 Kg (STK)
Skupina produktov	9
Colný sadzobník	73072980

Pokyny na použitie

kein Verwendungshinweis notwendig